

Technical sheet :

MLA 4-50 H



Capacities		Metric
Static tipping load with bucket (straight)		1839 kg
Static tipping load with bucket (full turn)		1205 kg
Static tipping load with forks (straight)		1480 kg
Static tipping load with forks (full turn)		971 kg
Max. height of bucket pivot point	h35	3.01 m
Max. lifting height (below forks)	h3	2.77 m
Breakout force with bucket		2412 daN
Weight and dimensions		
Unladen weight (with forks) with 2-post canopy		2740 kg
Unladen weight (with forks) with 4-post canopy		2790 kg
Ground clearance	m4	0.25 m
Overall length to carriage (with hitch)	l11	3.55 m
Overall length to carriage (without hitch)	l3	3.55 m
Wheelbase	y	1.62 mm
Overall width of 2 posts canopy	b21	1.01 m
Overall width of 4 posts canopy	b22	1.02 m
Overall width (over tyres)	b1	1.33 m
Overall height with FOPS removed and ROPS folded	h36	1.84 m
Overall height with 2 posts canopy	h37	2.54 m
Overall height with 4 posts canopy	h38	2.32 m
Overall height with cab	h17	2.32 m
Tilt-up angle	a4	45 °
Tilt-down angle	a5	53 °
Articulation angle		45 °
Engine		
Engine brand		Yanmar
Environmental norm		Stage 3A
Engine model		4TNV88
Number of cylinders / Capacity of cylinders		4 - 2200 cm³
I.C. Engine power rating / Power (kW)		47 Hp / 35 kW
Max. torque / Engine rotation		1680 Nm/m / 137 rpm
Engine cooling system		2 radiators water + hydraulic oil
Transmission		
Transmission type		Hydrostatic
Number of gears (forward / reverse)		2 / 2
Max. travel speed (may vary according to applicable regulations)		20 km/h
Differential lock		Machine Lock Rear & front
Parking brake		Manual
Hydraulics		
Hydraulic pump type		Gear pump
Hydraulic flow - Pressure		57 l/min / 207 Bar
Drive hydraulic system pressure		410 Bar
Tank capacities		
Hydraulic oil		42 l
Fuel tank		68 l
Noise and vibration		
Vibration to whole hand/arm		< 2.5 m/s²
Miscellaneous		
Safety cab homologation		Cab ROPS - FOPS Level 1

Options / Finishing

S : Standard / O : Optional / - : Not available

	Essential
Lifting function	
Easy Connect System (E.C.S.)	S
Hydraulic attachment locking	O
Operator station	
Adjustable and telescopic steering column	S

Air suspension seat

Canopy

Suspension Seat - Mechanical

Motorization/Power

Attachment hydraulic line

Continuous flow hydraulics

Hand throttle

Self cleaning air prefilter

Lighting

Complete road lighting

Flat LED rotating beacon (-71 mm)

Front and rear work lights on cab (x4: 2 front + 2 rear)

Essential

O

S

S

S

S

S




S


O

O

S

Dimensional drawing





Siège Social
430 rue de l'Aubinière - 44150 Ancenis Cedex - France
Tel: +33(0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97
www.manitou.com



This brochure describes versions and configuration options for Manitou products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Manitou reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Manitou dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Manitou and may not be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508
RCS Nantes